## SMDZ-CL40

## 40L SINGLE COMPARTMENT PORTABLE FRIDGE/FREEZER AC/DC STAINLESS STEEL

|  | Dimensions (mm) Unit:<br>(H) 520 (L) 625 (W) 460       |  |
|--|--|--|
|  | Storage Volume:<br><b>40L</b>                          |  |
| <b>*</b>   | Temp Range:<br>-22°C to 10°C                           |  |
| Ō  | Net Weight:<br>24Kg                                    |  |
|  | Compressor:<br><b>45W</b>                              |  |
| \$   | Rated Current:<br>3.75A (12V)<br>0.42A (220V)          |  |
|  | Cyclopentane Insulation:<br>60mm                       |  |
| The second secon | Voltage:<br>AC: <b>230V/50Hz</b><br>DC: <b>12V/24V</b> |  |
|  | Engineered for the<br>African climate                  |  |



## FEATURES

- Single Compartment
- Stainless Steel
- 3 Speed Setting High, Auto & Low
- SnoMaster<sup>®</sup> Compressor
- Interchangeable Temperature Controller
- Low Voltage Cut Out Setting (10, 10.7, 11.8V)
- Corner Feet with Mounting Holes
- Secure Mini Anderson Input & Output Plugs
- Internal LED Light
- Removable/Reversible Lid (Sliding Hinges)
- Lid Open Alarm
- Stainless Steel Hinges, Locks and Handles
- Includes: Baskets, Bottle Opener, Solar
  Powered Remote Control and Transit Cover

Note: All Dimensions Include Handles, Locks And Hinges; And Exlclude The Transit Cover. Maintain a 150mm clearance around the unit, ensuring adequate air circulation. Avoid tilting the appliance more than 45-degrees from its upright position.





Scan QR Code For More Information