## SMDZ-CL56D

## 56L DUAL COMPARTMENT PORTABLE FRIDGE/FREEZER AC/DC STAINLESS STEEL



Dimensions (mm) Unit:

(H) 515 (L) 755 (W) 500



Storage Volume:

56L (Left: 26L, Right: 30L)



Temp Range:

-22°C to 10°C



Net Weight:

28Kg



Compressor:

**70W** 



Rated Current:

5.92A (12V) 0.52A (220V)



Cyclopentane Insulation:

60<sub>mm</sub>



Voltage:

AC: 230V/50Hz DC: 12V/24V



**Engineered for the African climate** 



## FEATURES

- Dual Compartment
- Stainless Steel
- 3 Speed Setting High, Auto & Low
- SnoMaster® Compressor
- ✓ Interchangeable Temperature Controller
- ✓ Low Voltage Cut Out Setting (10, 10.7, 11.8V)
- Corner Feet with Mounting Holes
- Secure Mini Anderson Input & Output Plugs
- Internal LED Light
- ✓ Removable Lid (Sliding Hinges)
- Lid Open Alarm
- Stainless Steel Hinges, Locks and Handles
- Includes: Baskets, Bottle Opener, Solar
  Powered Remote Control and Transit Cover

Note: All Dimensions Include Handles, Locks And Hinges; And Exlclude The Transit Cover. Maintain a 150mm clearance around the unit, ensuring adequate air circulation. Avoid tilting the appliance more than 45-degrees from its upright position.





