80L SINGLE COMPARTMENT PORTABLE FRIDGE/FREEZER AC/DC STAINLESS STEEL



Dimensions (mm) Unit:

(H) 600 (L) 755 (W) 505



Storage Volume:

80L



Temp Range:

-22°C to 10°C



Net Weight:

30Kg



Compressor:

70W



Rated Current:

5.92A (12V) 0.52A (220V)



Cyclopentane Insulation:

60_{mm}



Voltage:

AC: 230V/50Hz DC: 12V/24V



Engineered for the African climate



FEATURES

- Single Compartment
- Stainless Steel
- 3 Speed Settings High, Auto & Low
- SnoMaster® Compressor
- ✓ Interchangeable Temperature Controller
- ✓ Low Voltage Cut Out Setting (10, 10.7, 11.8V)
- Corner Feet with Mounting Holes
- ✓ Secure Mini Anderson Input & Output Plugs
- Internal LED Light
- ✓ Removable Lid (Sliding Hinges)
- Lid Open Alarm
- Stainless Steel Hinges, Locks and Handles
- Includes: Baskets, Bottle Opener, Solar
 Powered Remote Control and Transit Cover

Note: All Dimensions Include Handles, Locks And Hinges; And Exlclude The Transit Cover. Maintain a 150mm clearance around the unit, ensuring adequate air circulation. Avoid tilting the appliance more than 45-degrees from its upright position.





