## SMDZ-TR42S

## 42L SINGLE COMPARTMENT PORTABLE FRIDGE/FREEZER AC/DC STAINLESS STEEL

8	Dimensions (mm) Unit: (H) 520 (L) 365 (W) 680	
	Storage Volume: <b>42L</b>	
<b>*</b>	Temp Range: -22°C to 10°C	(
Ø	Net Weight: 23.5Kg	
	Compressor: 45W	· ·
\$	Rated Current: 3.75A (12V) 0.42A (220V)	* * * * * * * * * * *
	Polyurethane Insulation: <b>50mm</b>	<b>* * *</b>
	Voltage: AC: <b>230V/50Hz</b> DC: <b>12V/24V</b>	× × ×
	Engineered for the African climate	



## FEATURES

- Single Compartment
- Stainless Steel
- 3 Speed Setting High, Auto & Low
- SnoMaster<sup>®</sup> Compressor
- Low Voltage Cut Out Setting (10, 10.7, 11.8V)
- Corner Feet with Mounting Holes
- Secure Mini Anderson Input & Output Plugs
- Internal LED Light
- Fixed Hinged Lid
- Lid Open Alarm
- Stainless Steel Hinges, Locks and Handles
- Includes: Baskets, Bottle Opener, Solar
  Powered Remote Control and Transit Cover

Note: All Dimensions Include Handles, Locks And Hinges; And Exlclude The Transit Cover. Maintain a 150mm clearance around the unit, ensuring adequate air circulation. Avoid tilting the appliance more than 45-degrees from its upright position.





Scan QR Code For More Information