SMLS-80D

60 Litre Sliding Single Compartment Mobile Fridge and Freezer
AC/DC Stainless Steel

SCAN FOR PRODUCT INFO

FLIP-UP LID
Top access to the compartment

DIGITAL TEMPERATURE CONTROL
Top panel beside the lid hinge

FRONT SLIDING DOOR
Pull-out drawer access

STORAGE BASKETS
Organised access to contents



SINGLE COMPARTMENT
One shared cooling zone

INTERNAL LED LIGHT
Illuminates the interior

CARRY HANDLES
Handles fitted to the exterior

304 STAINLESS STEEL
Exterior body

AC & DC POWER SUPPLY

DIMENSIONS H × W × D
457 × 800 × 453 mm

RATED POWER
85 W

STORAGE VOLUME
60 L

RATED CURRENT
DC 12V: 7.5A | 24V: 3.7A
AC: 1.6A-0.85A

TEMPERATURE RANGE
-20°C to 20°C

PU INSULATION
CFC-Free PU Foam

NET WEIGHT
23.9 kg

VOLTAGE
AC 100-240V | DC 12V/24V

2-SPEED SETTINGS
Max and Eco Mode

12V LOW-VOLTAGE CUT-OUT
11.1 / 10.4 / 8.5 V

30° TILT PROTECTION

DESIGNED FOR
African Conditions

SnoMaster®

Allow 60 mm ventilation clearance at front, back and sides. Follow the user manual.

snomaster.co.za